LandAirSea 54

Real Time GPS Asset Tracker Compact, Waterproof, Internal Magnet



The LandAirSea 54 GPS device helps you keep up to date on your most important assets. Featuring a compact, waterproof design with a built-in super-strength magnet, the device is small enough to attach to vehicles or placed into pockets, purses, bags, and backpacks. Receive notification alerts, track the device's location on a map, and view historical playback.



SPECIFICATIONS

WIRELESS COMMUNICATION

Multi-Mode 4G LTE CAT M1 / 4G LTE CAT NB1 / EGPRS (2G)

Global Bands Cat M1/NB1: B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B26/B28/B39

EGPRS: 850/900/1800/1900 MHz

Region Global

Carrier Certifications Vodafone / Deutsche Telekom / Telefónica / Verizon / AT&T / T-Mobile / Sprint /

U.S. Cellular / Rogers / Telus / KT / SKT / LGU+ / NTT DOCOMO / SoftBank /

KDDI / Telstra

Regulatory Certifications GCF / CE / FCC / PTCRB / IC / Anatel / IFETEL / CCC / KC / NCC / JATE / TELEC /

RCM / NBTC / IMDA

LOCATION SERVICES

GNSS GPS / GLONASS / BeiDou-Compass / Galileo / QZSS

Assisted GNSS Online

FEATURES

Waterproof Design / IP67 rated

Integrated built-in high strength magnet

Extremely powerful GNSS and Cellular Antennas designed for non-ideal conditions

Permanent Power Connection (Hard Wired) Waterproof Cable Option

Engine run-time monitoring and reporting (Hours of Operation)

Temperature monitoring and reporting

Selectable real time location updates as fast as every 2 seconds

Alarm Mode Scheduler for high theft risk hours

ShareSpot (Share the device location via text or email to anyone easily)

InstaFence (Instant notification if the asset leaves the current location)

Dark Mode (Remotely turn all LED's off)

Historical Playback (Bread crumbs)

Full API catalog for customized system integration



ENVIRONMENTAL DATA

Operational temperature -40° C to 60° C Storage temperature -40° C to 60° C

Humidity < 95% non-condensing Drop 3 feet onto concrete

Sealing Waterproof to IP67 standards

RoHS compliant (lead-free) Green (halogen-free)

BATTERY

Internal Battery Li-On rechargeable, 3.7V, 1500mAh

Charging / Input Voltage 4.5 - 5.5V
Charging Port USB Micro B

Battery Charge Time Approximately 6 hours from 0-100% at 25°C

BATTERY LIFE

Motion Tracking Mode (Tracks all movements at programmed frequency)

Update Frequency	Estimated <u>Driving Hours</u> Battery Life
3 Minutes	40 hours
1 Minute	37 hours
30 Second	35 hours
10 Second	30 hours
5 Second	26 hours
3 Second	24 hours

<u>Timer Based Tracking / Energy Saver Mode (Location updated at a set frequency)</u>

Reporting Frequency	Estimated Battery Life
24 Hours	365 days
12 Hours	250 days
8 Hour	180 days
6 Hour	140 days
4 Hour	90 days
2 Hour	60 days
1 Hour	30 days
30 Minute	15 days



INDICATOR / BUTTONS

LED 3 LED programmable (Battery, LTE Connectivity, GPS)

On/Off/Reset Button Touch Pin Sensitive (Power – Shortpress / Reset Hold 5 second)

PHYSICAL CHARACTERISTICS

Grade Industrial

Dimensions D: 2.275 in. H: 0.945 in.

Weight 75g







